

Applicant : Smits, et al.
Appl. No. : 09/479,548
Examiner : N/A
Docket No. : 8668.2029

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the application:

1-27 (Previously Cancelled)

28. (Cancelled)

29. (Previously Added) A device for hearing evaluation of a subject comprising:
means for repeatedly delivering an auditory stimulus;
means for sampling an EEG response to said stimulus; and
means for detecting when non-physiological noise is associated with said EEG

response.

30. (Previously Added) The device according to claim 29, further comprising
means for indicating when said non-physiological noise has been detected.

31. (Previously Added) A device for hearing evaluation of a subject comprising:
means for repeatedly delivering an auditory stimulus;
means for sampling an EEG response to said stimulus; and
means for detecting when non-physiological noise is associated with said EEG
response, for automatically determining the amount of said non-physiological noise, and for
automatically determining when said amount is excessive relative to a threshold.

32. (Previously Added) The device according to claim 31, wherein said threshold
is derived from normative data.

33. (Previously Added) A device for hearing evaluation of a subject comprising:
means for repeatedly delivering an auditory stimulus;

Applicant	:	Smits, et al.
Appl. No.	:	09/479,548
Examiner	:	N/A
Docket No.	:	8668.2029

means for sampling an EEG response to said stimulus, said EEG response including a noise component;

means for determining the polarity bias of said noise component; and

means for detecting the degree of polarity bias in said noise component, and for determining when said bias is excessive relative to a threshold.

34. (Previously Added) The device according to claim 33, wherein said threshold is derived from normative data.

35. (Cancelled)

36. (Amended) A device for hearing evaluation of a subject comprising:

means for repeatedly delivering an auditory stimulus;

means for sampling an EEG response to said stimulus; and

means for detecting the ambient acoustic noise associated with said EEG response,

for determining the signal energy of said ambient acoustic noise, and for determining if said signal energy is excessive relative to a threshold;

[The device according to claim 35,] where the means for detecting the ambient acoustic noise is a microphone.

37. (Previously Added) The device according to claim 36, where the means for determining if the signal energy associated with the ambient acoustic noise is excessive relative to a threshold operates by taking samples of the ambient acoustic noise at a time that interferes with the delivery of the stimulus.

38. (Previously Added) The device according to claim 37, where the means for determining if the signal energy associated with the ambient acoustic noise is excessive

Applicant : Smits, et al.
Appl. No. : 09/479,548
Examiner : N/A
Docket No. : 8668.2029

relative to a threshold operates by taking samples of the ambient acoustic noise both before and during the time that the auditory stimulus is delivered.

39. (Previously Added) The device according to claim 38, where the means for determining if the signal energy associated with the ambient acoustic noise is excessive relative to a threshold operates by analyzing a weighted energy sum of said samples.

40. (Previously Added) A device for hearing evaluation of a subject comprising:
means for repeatedly delivering an auditory stimulus;
means for sampling an EEG response to said stimulus, said EEG response including a noise component;
means for detecting the magnitude of said noise component;
means for determining the polarity bias of said noise component;
means for determining when adverse evaluation conditions are present, based upon both said noise magnitude and said noise polarity bias.

41. (Amended) The device according to claim [28,] 29, 31, 33, [35] 36, or 40, further comprising means for determining the presence of an ABR waveform.

42. (Cancelled)

43. (Amended) A method for hearing evaluation of a subject, comprising the steps of

repeatedly delivering an auditory stimulus;

measuring the EEG response to said stimulus;

detecting the noise associated with said EEG response;

automatically detecting the amount of said noise; and

automatically determining that said amount is excessive relative to a threshold;

Applicant : Smits, et al.
Appl. No. : 09/479,548
Examiner : N/A
Docket No. : 8668.2029

[The method according to claim 42,] wherein automatically determining that said noise amount is excessive relative to a threshold comprises computing a composite signal noise variance.

44. (Previously Added) The method according to claim 43, wherein automatically determining that said noise amount is excessive relative to a threshold further comprises comparing the composite signal noise variance to a predetermined threshold, and determining that the composite signal noise variance is greater than said threshold.

45. (Previously Added) The method according to claim 44, further comprising the step of pausing the testing in response to determining that said noise amount is excessive relative to a threshold.

46. (Previously Added) The method according to claim 45, further comprising the step of determining if said EEG response contains an ABR waveform.

47. (Previously Added) A method for hearing evaluation of a subject, comprising the steps of

repeatedly delivering an auditory stimulus;

measuring EEG responses to said stimulus, said EEG responses having amplitudes;

detecting noise associated with said EEG responses;

determining a degree of polarity bias in said noise; and

determining when said bias is excessive relative to a threshold.

48. (Previously Added) The method according to claim 47, whereby determining when said polarity bias is excessive relative to a threshold comprises:

digitizing said EEG response;

Applicant	:	Smits, et al.
Appl. No.	:	09/479,548
Examiner	:	N/A
Docket No.	:	8668.2029

transforming said digitized EEG response into a series of binary numbers corresponding to the polarity of the amplitude of said EEG response;

transforming said binary numbers into an array of polarity sums;

determining the bias in said array of polarity sums; and

comparing said bias to a predetermined threshold.

49. (Previously Added) The method according to claim 47, whereby determining when said polarity bias is excessive relative to a threshold comprises:

determining the difference between the mean and the median amplitude in said EEG responses; and

comparing said difference to a predetermined threshold.

50. (Previously Added) The method according to claim 47, further comprising the step of pausing the testing in response to detecting excessive levels of polarity bias in said noise.

51. (Previously Added) The method according to claim 47, further comprising the step of determining if said EEG response contains an ABR waveform.

52. (Previously Added) A method for hearing evaluation of a subject, comprising the steps of

repeatedly delivering an auditory stimulus;

measuring EEG response to said stimulus;

detecting the noise associated with said EEG response;

determining the amount of said noise;

determining the degree of polarity bias in said noise;

Applicant : Smits, et al.
Appl. No. : 09/479,548
Examiner : N/A
Docket No. : 8668.2029

determining when adverse evaluation conditions are present, based upon both said noise amount and said noise polarity bias.

53. (Cancelled)

54. (Amended) A method for hearing evaluation of a subject which comprises the steps of

repeatedly delivering an auditory stimulus to a subject;
measuring an EEG response to the stimulus said response having a amplitude
polarity at each point in time;
digitizing said EEG response;
transforming said digitized EEG response into a series of binary numbers
corresponding to the polarity of the amplitude of said EEG response;
transforming said binary numbers into an array of polarity sums;
detecting the noise associated with said EEG response;
determining the amount of said noise;
automatically detecting when said amount is excessive relative to a threshold;
accounting for any excessive amounts of said noise; and
determining if an EEG response contains an ABR waveform by comparing the array
of polarity sums against normative data;

[The method according to claim 53,] wherein the step of accounting for excessive amounts of said noise comprises pausing the evaluation.

55. (Amended) A method for hearing evaluation of a subject which comprises the steps of

repeatedly delivering an auditory stimulus to a subject;

Applicant : Smits, et al.
Appl. No. : 09/479,548
Examiner : N/A
Docket No. : 8668.2029

measuring an EEG response to the stimulus said response having a amplitude
polarity at each point in time;
digitizing said EEG response;
transforming said digitized EEG response into a series of binary numbers
corresponding to the polarity of the amplitude of said EEG response;
transforming said binary numbers into an array of polarity sums;
detecting the noise associated with said EEG response;
determining the amount of said noise;
automatically detecting when said amount is excessive relative to a threshold;
accounting for any excessive amounts of said noise; and
determining if an EEG response contains an ABR waveform by comparing the array
of polarity sums against normative data;

[The method according to claim 53,] wherein the step of accounting for excessive amounts of said noise comprises rejecting a portion of said array of polarity sums.

56. (Previously Added) A method of evaluation for hearing loss which comprises the steps of

repeatedly delivering an auditory stimulus to a subject;
measuring an EEG response to the stimulus said response having an amplitude
polarity at each point in time;
digitizing said EEG response;
transforming said digitized EEG response into a series of binary numbers
corresponding to the polarity of the amplitude of said EEG response;
transforming said binary numbers into an array of polarity sums;

Applicant	:	Smits, et al.
Appl. No.	:	09/479,548
Examiner	:	N/A
Docket No.	:	8668.2029

detecting the noise associated with said EEG response;

detecting the degree of polarity bias in said noise;

determining when said bias is excessive relative to a threshold;

accounting for any excessive bias; and

determining if an EEG response contains an ABR waveform by comparing the array of polarity sums against normative data.

57. (Previously Added) The method according to claim 56, wherein the step of accounting for any excessive polarity bias comprises pausing the evaluation.

58. (Previously Added) The method according to claim 56, wherein the step of accounting for any excessive polarity bias comprises rejecting a portion of said array of polarity sums.

59. (Cancelled)

60. (Amended) A method for evaluation for hearing loss comprising the steps of repeatedly delivering an auditory stimulus to a subject;
measuring an EEG response to the stimulus;
detecting the ambient acoustic noise associated with said EEG response;
determining the signal energy of said ambient acoustic noise; and
determining if said signal energy exceeds a predetermined threshold;

[The method according to claim 59,] wherein the ambient acoustic noise is sampled both before and during the time the auditory stimulus is delivered.

61. (Amended) A method for evaluation for hearing loss comprising the steps of repeatedly delivering an auditory stimulus to a subject;
measuring an EEG response to the stimulus;

Applicant : Smits, et al.
Appl. No. : 09/479,548
Examiner : N/A
Docket No. : 8668.2029

detecting the ambient acoustic noise associated with said EEG response;

determining the signal energy of said ambient acoustic noise; and

determining if said signal energy exceeds a predetermined threshold;

[The method according to claim 59,] wherein the ambient acoustic noise is sampled before the auditory stimulus is delivered.

62. (Amended) A method for evaluation for hearing loss comprising the steps of repeatedly delivering an auditory stimulus to a subject;

measuring an EEG response to the stimulus;

detecting the ambient acoustic noise associated with said EEG response;

determining the signal energy of said ambient acoustic noise; and

determining if said signal energy exceeds a predetermined threshold;

[The method according to claim 59,] wherein the ambient acoustic noise is sampled during the time the auditory stimulus is delivered.

63. (Previously Added) The method according to claim 60, wherein the samples are taken during three, approximately 20 millisecond windows of time.

64. (Previously Added) A system for hearing evaluation of a subject comprising:

a transducer having an audible click output stimulus;

an electrode system adapted to detect an EEG response to said stimulus; and

a processor, responsive to said EEG response, having

means for sampling the EEG response;

means for processing the sampled EEG response and identifying therein a noise component and an evoked ABR component; and

Applicant	:	Smits, et al.
Appl. No.	:	09/479,548
Examiner	:	N/A
Docket No.	:	8668.2029

means for automatically determining when said noise component contains a non-physiological component.

65. (Cancelled)